



There are 6 available options:

- 1.T30BS — Manual start, tiller/back control, short shaft
- 2.T30BL — Manual start, tiller/back control, long shaft
- 3.T30BWS — Electric start, tiller/back control, short shaft
- 4.T30BWL — Electric start, tiller/back control, long shaft
- 5.T30FWS — Electric start, remote/front control, short shaft
- 6.T30FWL — Electric start, remote/front control, long shaft

Type	T30BS	T30BL	T30BWS	T30BWL	T30FWS	T30FWL
Length (mm)	843	843	843	843	608	608
Width (mm)	399	399	399	399	358	358
Height (mm)	1146	1273	1146	1273	1146	1273
Dry Weight (kg)	53.00	54.50	56.50	58.00	55.00	56.50
Transom Height (mm)	423	550	423	550	423	550
Rated Power (kw)	22.1	22.1	22.1	22.1	22.1	22.1
Max RPM (Revolutions/min)	4500-5500	4500-5500	4500-5500	4500-5500	4500-5500	4500-5500
Stroke	2	2	2	2	2	2
Number of Cylinders	2	2	2	2	2	2
Bore x Stroke	72*61	72*61	72*61	72*61	72*61	72*61
Displacement (cc)	496	496	496	496	496	496
Exhaust System	Center Exhaust	Center Exhaust	Center Exhaust	Center Exhaust	Center Exhaust	Center Exhaust
Cooling System	Water Cooling	Water Cooling	Water Cooling	Water Cooling	Water Cooling	Water Cooling
Starting System	Manual	Manual	Manual / Electric	Manual / Electric	Manual / Electric	Manual / Electric
Steering System	Tiller	Tiller	Tiller	Tiller	Remote	Remote
Ignition System	CDI	CDI	CDI	CDI	CDI	CDI
Spark Plug	BR8HS-10	BR8HS-10	BR8HS-10	BR8HS-10	BR8HS-10	BR8HS-10
Fuel Tank	24L	24L	24L	24L	24L	24L
Gear Ratio	2.08(27/13)	2.08(27/13)	2.08(27/13)	2.08(27/13)	2.08(27/13)	2.08(27/13)
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
Propeller	9 7/8×12-F	9 7/8×12-F	9 7/8×12-F	9 7/8×12-F	9 7/8×12-F	9 7/8×12-F
Idle Speed (r/min)	1150±50	1150±50	1150±50	1150±50	1150±50	1150±50